





# PLH-Pure Lead Punched Grid PLH190FT(A) (12V190Ah)

## Specifications

Rated Voltage	12V	
Nominal Capacity	C <sub>10</sub> , 1.80V/cell	190Ah
	C <sub>8</sub> , 1.75V/cell	190Ah
Dimension	Length	559±3mm (22.01 inches)
	Width	125±2mm (4.92 inches)
	Container Height	320±3mm (12.6 inches)
	Total Height	320±3mm (12.6 inches)
Approx. Weight	57.6 Kg (127.0 lbs)	
Terminal	M6	
Container Material	PC-ABS flame retardant jar and cover to UL94 V-0	
Rated Capacity (25°C)	199.6 Ah	(20hr, 9.98A, 1.80V/cell)
	190.0 Ah	(10hr, 19.0A, 1.80V/cell)
	173.0 Ah	(5hr, 34.6A, 1.75V/cell)
	166.8 Ah	(3hr, 55.6A, 1.75V/cell)
	138.9 Ah	(1hr, 138.9A, 1.67V/cell)
Max. Discharge Current	2280A	
Internal Resistance (25°C)	Approx. 3.0mΩ(Fully charged)	
Operating Temp. Range	Discharge	-40 ~ 65°C (-40 ~ 149°F)
	Charge	0 ~ 40°C (32 ~ 104°F)
	Storage	-20 ~ 40°C (-4 ~ 104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Max. Charging Current(25°C)	57.0A	
Charge voltage(25°C)	Float	13.62V
	Temp. Coefficient	-3mV/cell/°C
	Equalization	14.1~14.4V
Effect of temp. to Capacity	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	<p>PLH series batteries can be stored up to 24 months at 25°C(77°F), For higher temperatures the time interval will be shorter.</p> <p>Battery needs to be given a freshening charge when the OCV approach 2.10V/cell or when the maximum storage time is reached, whichever occurs first.</p>	



## Layout



Unit: mm

## Constant Current Discharge (Amperes) at 25 °C (77° F)


F.V/Time	10 min	15min	20min	30min	45min	1h	2h	3h	4h	5h	8h	10h	20h
1.85V/cell	341.5	292.9	249.5	195.0	149.8	123.1	73.3	52.8	41.2	33.1	22.6	18.4	9.67
1.80V/cell	377.8	321.9	267.1	210.0	158.3	128.7	76.2	54.6	42.1	34.0	23.4	19.0	9.98
1.75V/cell	408.5	343.7	282.3	218.8	162.5	133.7	77.8	55.6	43.1	34.6	23.8	19.2	10.1
1.70V/cell	434.6	359.7	295.2	226.0	167.3	136.8	78.9	56.3	43.5	35.0	23.9	19.4	10.1
1.67V/cell	456.3	372.5	301.7	231.0	170.3	138.9	79.5	57.1	43.7	35.2	24.0	19.5	10.2
1.60V/cell	482.0	391.2	311.9	236.2	174.7	140.2	80.2	58.0	44.1	35.4	24.1	19.7	10.3

## Constant Power Discharge (Watts/cell) at 25 °C (77° F)

F.V/Time	10 min	15min	20min	30min	45min	1h	2h	3h	4h	5h	8h	10h	20h
1.85V/cell	647.5	560.5	480.0	379.7	295.6	243.6	145.7	105.5	82.4	66.5	46.5	37.5	19.7
1.80V/cell	705.2	607.9	509.1	406.1	311.0	253.5	151.2	108.9	84.2	68.6	47.3	38.6	20.3
1.75V/cell	755.0	642.7	533.5	419.9	316.9	261.8	153.7	110.9	86.0	69.2	47.9	38.8	20.5
1.70V/cell	790.7	664.0	552.0	429.9	324.3	267.0	155.9	111.8	86.6	69.8	47.9	39.0	20.6
1.67V/cell	822.0	690.5	560.0	437.9	329.0	269.6	156.5	113.1	87.0	70.0	48.1	39.1	20.6
1.60V/cell	845.3	700.5	569.2	442.0	333.3	269.9	158.5	114.8	87.5	70.5	48.3	39.8	20.6



# PLH-Pure Lead Punched Grid PLH190FT(A) (12V190Ah)



## Applications

- Telecommunication
- Railway signal
- Alarm and security system
- Power station systems
- Emergency power supply


## General Features

- 20 years design life(25°C)
- Premium ABS+PC jar & covers, Flame Retardant to UL94 V-0
- High-rate performance, high energy density
- High quality AGM separators minimize electrical resistance to allow high current discharging properties


## Standards

- Meets Telcordia® NEBS™ Level III, GR63 Requirements
- Classified as "Very Long Life" according to Eurobat IEC 60896-21 & 22
- CE, UL Certified
- Manufactured in LEOCH® IATF16949, OSHAS 18001, ISO 9001 and ISO 14001 Certified Production Facilities


## Discharge Characteristics




## Float Charging Characteristics



## Effects of Temperature on Discharging Time



## Float Life



## Sales Offices Worldwide

### China Sales Office

5th Floor, Xinbaohui Bldg., Nanhai Blvd.,  
Nanshan, Shenzhen, China. 518052  
Tel: +86-755-86036060 (100 lines)  
Fax: +86-755-26067269  
E-mail: export@leoch.com

### HongKong Sales Office

Workshop C, 33/F, TML Tower, No. 3 Hoi Shing Road,  
Tsuen Wan, New Territories, Hong Kong  
Tel: +852 35786666  
Fax: +44 1452 690125  
E-mail: sales.hk@leoch.com

### Singapore Sales Office

No. 1 Tech Park Crescent,  
Singapore 638131  
Tel: +65 68636078  
Fax: +65 6863 6079  
Email: sales.sg@Leoch.com

### Australia Sales Office

2 /29 Tarlington Place, Smithfield, NSW 2164  
Australia  
Tel: 02 9756 0950  
E-mail: sales.au@leoch.com

### North America Sales Office

19751 Descartes  
Foothill Ranch, CA 92610, USA  
Tel: 949-588-5853  
Fax: 949-588-5966  
E-mail: sales@leoch.us

### UK Sales Office

9B Wheatstone Court, Waterwells, Business Park,  
Gloucester, GL2-2AQ, UK United Kingdom  
Tel: +44(0) 1452 729428 / 1452 729696  
Fax: +44 1452 690125  
E-mail: Sales.Europe@leoch.com

### EMEA Sales Office

1 Deligiorgi St., 121 31 Athens,  
Greece  
Tel: +30 210 5760318 (2 lines)  
E-mail: support\_EMEA@leoch.com

### India Sales Office

Shed no.A-53(b), 2nd Stage of Peenya Industrial Area,  
Bangalore North Taluk, Bangalore-560058, India  
Tel: +91-80-23440018/23440019  
Fax: +91-80-23440017  
E-mail: indiasales@leoch.com



[Http://www.leoch.com](http://www.leoch.com)  
[Http://www.leoch.us](http://www.leoch.us)

© 2019 LEOCH. All rights reserved.

Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.  
Subject to revisions without prior notice.

Publication No.: LB-PLH190FT(A)-PD-EN-V3.3-201904